



SharPro LED Driver

---the best with the same price, the cheapest with the same quality.

| Item | Image | Description | V (input) (AC) | V (output) (DC) | Current (mA) | Size (mm) | Price (RMB) |
|---------------------------------------|-------|--|-------------------|--------------------|-------------------|--------------|---------------------|
| 1-3*1W | | Applications: Bulbs, Ceiling light, Panel light | 85-265Vac | DC:3-12V | 250mA 300mA±5% | L24.5×W16 | 1.9 |
| 1-3*1W | | Applications: Bulbs, Ceiling light, Panel light | 85-265Vac | DC:3-12V | 250mA 300mA±5% | L33×W20 | 2.6 |
| 1-3*1W | | Applications: Candle light | 85-265Vac | DC:3-12V | 250mA 300mA±5% | L29.2×W11 | 2.4 |
| 5*1W | | Applications: Bulbs, Ceiling light, Panel light | 85-265Vac | DC:8-18V | 250mA 300mA±5% | L31×W16 | 2.4 |
| 4-7*1W | | Applications: Bulbs, Ceiling light, Panel light | 165-265Vac | DC:12-24V | 250mA 300mA±5% | L40×W17 | 3.1 |
| 8-12*1W | | Applications: Bulbs, Ceiling light, Panel light | 165-265Vac | DC:23-45V | 250mA 300mA±5% | L55×W22 | 4.5 |
| 12-18*1W | | Applications: Bulbs, Ceiling light, Panel light | 165-265V | DC:36-62V | 250mA 300mA±5% | L53×W23 | 5.7 |
| 18-30*1W | | Applications: Bulbs, Ceiling light, Panel light | 165-265V | DC:54-100V | 250mA 300mA±5% | L76×W27 | 16 |
| 8-18W tube light (non-isolated) | | Applications: Tube light | 165-265Vac | DC:60-150V | 120mA 250mA±5% | L65×W15 | 3.38 3.8 (250mA) |

| | | | | | | | |
|---|--|--|------------|------------|-------------------|---------|--------------------------------|
| 8-18W tube light (non-isolated) |  | Applications: Tube light(end cap), Bulbs | 165-265V | DC:24-80V | 240mA | L31×W21 | 3.3 |
| 8-18W ceiling light (non-isolated) |  | Applications: Ceiling light, kitchen light | 165-265Vac | DC:60-150V | 120mA | L33×W24 | 2.9 |
| 8-30W Ceiling light |  | Applications: Ceiling light (Round) | 165-265V | DC:24-100V | 250mA 300mA±5% | L46×W28 | 4.3 |
| 8-36W Remote control Driver (Round) |  | Applications: three step control ceiling light (Round) | 175-265V | DC:24-110V | 260mA±5% | Ø60mm | 10 (Controller excluded) |
| 8-36W Remote control Driver (Square) |  | Applications: three step control ceiling light (Square) | 175-265V | DC:24-110V | 260mA±5% | L80×W35 | 10 (Controller excluded) |
| 12-24W Wifi Control |  | Applications: Wifi Control bulbs | 175-265V | DC:54-80V | 260mA±5% | L85×W35 | 33 (Controller excluded) |

All above tax excluded



Sharpro
祥普照明

营销总监 **李芳**
EMO Tina Li

中山市祥普照明科技有限公司
ZhongShan SharPro Lighting Technology Co.,Ltd

地址/Add: 中山市古镇镇曹二曹兴东路94号5楼
手机/Tel: 18022120478 QQ:565404264
电话/Fax: 0760-89859089 传真/Fax: 0760-22180069
邮箱/EMail: 565404264@qq.com
网站/Http: www.sharpro.com 微信号:sharproled



全国免费热线
4008-525-088