PT62SCMD12

Dual 1200V SIC MOSFET driver

Features:

- **Designed for driving CREE CAS300M12BM2 SIC MOSFETS modules**
- **Low jitter: typical 1ns**
- **+20V/-6V gate driving**
- **Over-current protected**
- **Switching frequencies up to 125kHz**
- **Adjustable dead and blanking time**
- **Dead-time generator**
- **Output currents up to +/- 20A**
- **Under and over voltage lock out**
- **High dV/dt immunity**
- **No optocouplers**
- **RS422 input interface**
- **Large power supply range, from 15V up to 24V**

Driver ID	Associated SIC MOSFET module
PT62SCMD12 R01	**CAS300M12BM2**

Overview:



© 2014 Prodrive Technologies B.V.

1. Electrical characteristics

1.1. Operating range

Within the operating range the driver operates as described in the functional description. Unless otherwise noted all voltages refer to GND.

Table 1-1, Operating range

Item	Description	Min	Typ	Max	Unit	Remarks
V_{POWER}	Supply voltage	14.5	-	26	[V]	-
$V_{D,HIGH}$ $V_{D,LOW}$	Inputs OCP	0	-	1700	[V]	Referred to respectively GND_{HIGH} and GND_{LOW}
$\|V_{GND,HIGH}/dt\|$ $\|V_{GND,LOW}/dt\|$	Maximum voltage transients @ the secondary ground	-	-	100	kV/µs	-
T_{AMB}	Operating temperature range, no airflow	-40	-	85	[°C]	No condensation

1.2. Electrical characteristics

Table 1-2, Input power

Item	Description	Min	Typ	Max	Unit	Remarks
$P_{IN,OPERATIONAL}$	Power consumption PT62SCMD12[1)]	-	12	-	[W]	f_{SWITCH}=100kHz
$P_{IN,IDLE}$	Idle Power consumption PT62SCMD12	-	3.5	4	[W]	-

Note[1)] In combination with module CAS300M12BM2

Table 1-3, Differential RS422 inputs

Item	Description	Min	Typ	Max	Unit	Remarks
$V_{INX,X}$	Single ended input level	-7	-	12	[V]	-
$\Delta V_{IN,X}$	Differential input high-threshold voltage	0.7	-	-	[V]	$\Delta V_{IN,X} = \Delta V_{IN+,X} - \Delta V_{IN-,X}$
	Differential input low-threshold voltage	-	-	-0.2	[V]	
R_{ID}	Differential input impedance		120		[Ohm]	-

Table 1-4, Logic output

Item	Description	Min	Typ	Max	Unit	Remarks
V_{STATUS} = OK	Status output voltage when the status of the driver is OK	4.7	-	-	[V]	-
V_{STATUS} = NOK	Status output voltage when the status of the driver is NOK	-	-	0.8	[V]	-

Table 1-5, Gate drivers

Item	Description	Min	Typ	Max	Unit	Remarks
$V_{GATE,HIGH}$ = HIGH $V_{GATE,LOW}$ = HIGH	High level output voltage, V_{POWER}=24V	18	20	22	[V]	Referred to respectively GND_{HIGH} and GND_{LOW}
$V_{GATE,HIGH}$ = LOW $V_{GATE,LOW}$ = LOW	Low level output voltage, V_{POWER}=24V	-8	-6	-4	[V]	
$V_{GATE,HIGH}$ = HIGH $V_{GATE,LOW}$ = HIGH	Peak output current capability[1)]	20	-	-	[A]	-

Note[1)] With $R_{GATE,ON}$ = $R_{GATE,OFF}$ = 0Ohm

© 2014 Prodrive Technologies B.V.

Table 1-6, Reset

Item	Description	Min	Typ	Max	Unit	Remarks
V_{RESET}	Input voltage range RESET input	-0.3	-	6	[V]	-
V_{RESET} = HIGH	Reset high input voltage	3.5	-	-	[V]	-
V_{RESET} = LOW	Reset low input voltage	-	-	1.5	[V]	-
t_{RESET}	Pulse width of RESET for clearing errors	10	-	-	[us]	-

Table 1-7, Dynamical characteristics @ T_{AMB} = 25°C

Item	Description	Min	Typ	Max	Unit	Remarks
$t_{ON,PROP}$	Turn on propagation delay	-	100	125	[ns]	See section 1.2.1 for definitions
$t_{OFF,PROP}$	Turn off propagation delay	-	100	125	[ns]	
$t_{ON,RISE}$	Turn on rise time PT62SCMD12[1)]	-	400	500	[ns]	
$t_{OFF,FALL}$	Turn off fall time PT62SCMD12[1)]	-	250	300	[ns]	
Δt	Delay mismatch (high and low side turn on and off) [2)]	-	0.25	2.5	[ns]	
$\lvert t_{JITTER} \rvert$	Absolute jitter of turn off and turn on delay[2)]	-	1	2.5	[ns]	-
f_{SWITCH}	Switching frequency	DC	-	125	[kHz]	Limited by $P_{OUT,AVG}$
$t_{DEAD,PROG}$	Programmable dead time	0	-	1000	[ns]	See section 1.3.2 and section 4.4
$t_{BLANKING}$	Blanking time. This is the time in between turning on the MOSFET and monitoring the $V_{DS.}$	1	-	-	[us]	-
$t_{STARTUP}$	Start-up timing	-	75	100	[ms]	See section 1.2.1 for definitions

Note[1)] In combination with module CAS300M12BM2
Note[2)] Measured without connected module/load and $R_{GATE,ON}$ = $R_{GATE,OFF}$ = 0Ohm

1.2.1. Timing definitions



Figure 1-1, Propagation delay



Figure 1-2, Rise/fall time



Figure 1-3, Delay mismatch



Figure 1-4, Start-up timing

© 2014 Prodrive Technologies B.V.

1.3. Protections

1.3.1. Under Voltage Lock Out (UVLO)

Both secondary sides are equipped with an UVLO indirectly monitoring the gate voltages.

Table 1-8, UVLO

Item	Description	Min	Typ	Max	Unit	Remarks
$V_{UVLO,SEC}$	Secondary side under voltage lock out	16	18	-	[V]	Only positive voltage is monitored

The primary side is equipped with an UVLO and an OVLO (Over Voltage Lock Out) monitoring an internally generated supply voltage.

1.3.2. Dead-time generator

The driver has an on-board dead-time generator which overrules the input signals when the dead-time of the applied PWM signals ($t_{DEAD,IN}$) becomes larger than the set dead-time ($t_{DEAD,PROG}$). Note that when the dead-time generator has to intervene, the jitter increases to a maximum of 10ns.

The dead time is by default set at 500ns, but can be changed by modifying R901 and R902. See chapter 4 for application information.

Table 1-9 Dead time settings

R_{901}	R_{902}	t_{DEAD}	unit	Remarks
not assembled	not assembled	1000	[ns]	-
not assembled	assembled	500	[ns]	Default setting
assembled	not assembled	250	[ns]	-
assembled	assembled	-	[ns]	Dead time disabled

1.3.3. Over Current Protection (OCP)

The driver features V_{DS} monitoring for protecting the modules against overcurrent. Both the blanking time (time the monitor is not-active when switching on), as the V_{DS} level (proportional with I_{DS}) is user-adjustable.

Table 1-10 V_{DS} monitoring

Item	Description	Min	Typ	Max	Unit	Remarks
$V_{DS,TRIP}$	Default V_{DS} trip level PT62SCMD12	-	4	-	[V]	See *Figure 1-6*
$t_{BLANKING}$	Default Blanking time	0.75	1	1.25	[us]	
$t_{SHUTDOWN}$	Delay between a detected over current and a shutdown of the driver	-	-	1	[us]	
t_{STATUS}	Delay between an over current protection and a low going STATUS at the primary side.	-	-	100	[us]	-

© 2014 Prodrive Technologies B.V.



Figure 1-5, Timing V_{DS} monitor under nominal conditions



Figure 1-6, Timing V_{DS} monitor when an over current is detected

1.3.4. Errors and stating

In the table below the LED and the output status is listed for all situations.

Table 1-11 Optical status interfacing

State	PRIMARY SIDE ERROR	HIGH SIDE ERROR	LOW SIDE ERROR	LED PRIMARY SIDE		LED SECONDARY SIDE		OUTPUT STATUS	
				POWER	ERROR	HIGH	LOW	$V_{GATE,HIGH}$	$V_{GATE,LOW}$
Operational	-	-	-	●	OFF	●	●	As input	As input
Primary error	INIT error[2)]			◐	◐	OFF	OFF	0V	0V
	UVLO or OVP	-	-	OFF	◐	●	●	LOW	LOW
Secondary error	-	UVLO or OCP	-	●	◐	OFF	●	LOW	LOW
	-	-	UVLO or OCP	●	◐	●	OFF	LOW	LOW

Note[1)] The symbols ◐ and ◐ are representing blinking LED's
Note[2)] Initialization error of the driver

1.4. Gate resistance

The applied gate resistances are listed in the table below.

Table 1-12 Gate resistances

Item	Driver ID	unit
	PT62SCMD12	
$R_{GATE,ON}$	5	[Ohm]
$R_{GATE,OFF}$[1)]	2.5	[Ohm]
C_{GS}	18	[nF]

Note[1)] Note that the effective turn-off resistance is specified

© 2014 Prodrive Technologies B.V.

1.5. Electrical isolation

Table 1-13 Grade of insulation[1)]

Circuit	PRIMARY	SECUNDARY_LOW	SECUNDARY_HIGH
PRIMARY	-	BASIC	BASIC
SECUNDARY_LOW	BASIC	-	BASIC
SECUNDARY_HIGH	BASIC	BASIC	-

Note[1)] Based on NEN-EN-IEC 60950

Table 1-14 Clearance distances

Circuit	PRIMARY	SECUNDARY_LOW	SECUNDARY_HIGH
PRIMARY	-	11.6mm	11.6mm
SECUNDARY_LOW	11.6mm	-	6.2mm
SECUNDARY_HIGH	11.6mm	6.2mm	-

Table 1-15 Creepage distances

Circuit	PRIMARY	SECUNDARY_LOW	SECUNDARY_HIGH
PRIMARY	-	11.6mm	11.6mm
SECUNDARY_LOW	11.6mm	-	23.2mm
SECUNDARY_HIGH	11.6mm	23.2mm	-

A safety test is applied at every driver produced, used test parameters are listed below.

Table 1-16 Safety test

Item	Description	Min	Typ	Max	Unit	Remarks
V_{TEST}	Test voltage primary to secondary side	-	5	-	[kV_{DC}]	1s, non-repetitive

© 2014 Prodrive Technologies B.V.

2. Electrical interfaces

2.1. MOSFET terminals

Table 2-1 MOSFET terminals

Terminal ID	Mnemonic driver	Pinning @ MOSFET module	Connector style
X21	$V_{GATE,HIGH}$	4	Faston 2.8mm x 0.5mm receptacle
X22	GND_{HIGH}	5	
X23	$V_{DRAIN,HIGH}$	3	
X31	GND_{LOW}	7	
X32	$V_{GATE,LOW}$	6	
X33	$V_{DRAIN,LOW}$	1	

2.2. Input connector

Table 2-2 Input connector

Connector ID	Pin#	Mnemonic driver	Interface
X10	1	$V_{IN+,HIGH}$	2 x 4pin boxed header, angled, lockable & keyed. 2.54mm pitch 
	2	$V_{IN-,HIGH}$	
	3	RESET	
	4	GND	
	5	$V_{IN+,LOW}$	
	6	$V_{IN-,LOW}$	
	7	STATUS	
	8	V_{POWER}	

© 2014 Prodrive Technologies B.V.

3. Mechanical characteristics

Top view



Figure 3-1, Dimensions, top view

Bottom view



Figure 3-2, Bottom view

Side view



Figure 3-3, Dimensions, side view

© 2014 Prodrive Technologies B.V.

4. Application notes

4.1. Input connection.

Connector
For the input connector (X10) a boxed header from Wurth is applied (612 008 217 21), a possible mating wire connector is for example the 71600-608LF from FCI.

Wiring
For increasing the immunity of the PWM input signals the driver is equipped with differential inputs. For reaching maximum performance the differential pairs should be physically kept close to each other by using for example a flat cable with twisted differential pairs. 输入PWM最好用双绞差分线连接较好

Although the differential concept already gives additional immunity it is still recommended to keep the PWM signal lines away from conductors carrying large currents. Shielding of the wires will increase the immunity further. 将PWM线原理大电流线避免辐射干扰

4.2. Input power.

The ramp-up of the supply voltage during start-up should be smooth and no dips should occur. 跌落不允许



Figure 4-1, Behavior input voltage during start-up

4.3. Disabling OCP

If it, for any reason, is desired to disable the OCP then this can be achieved by interconnecting:

- X31 with X33 and
- X22 with X23

Note that when X23 and/or X33 are <u>not</u> connected the driver will always enter its error stated when PWM is applied.

© 2014 Prodrive Technologies B.V.

4.4. Modifying dead-time and OCP settings

In this section information is given for modifying dead time, V_{DS} trip level and/or blanking time.

Modifying dead-time

The dead time can be programmed by assembling the resistors R901 and R902 (0603 package). Values of the resistors should be 220Ohm or lower. The possible settings are listed below.



Figure 4-2, Location R901 and R902

© 2014 Prodrive Technologies B.V.

Modifying blanking time

The blanking time can be modified by changing C_{BLANK} (0603 package). Settings are listed below, locations are shown in *Figure 4-2*. For C_{BLANK} a capacitor with NP0 dielectric is recommended, the voltage rating should be at least 25V.

Table 4-1 $t_{BLANKING}$ setting

C_{BLANK}	$t_{,BLANKING}$	unit	Remarks
56pF	0.5	[us]	-
120pF	1	[us]	Default setting
390pF	3	[us]	-
560pF	5	[us]	-

Modifying $V_{DS,TRIP}$ setting

The V_{DS} trip-level can be modified by changing R_{OCP} (1206 package). Settings are listed below, locations are shown in *Figure 4-3*.

Table 4-2 $V_{DS,TRIP}$ setting PT62SCMD12

R_{OCP}	Unit	$V_{DS,TRIP}$	unit	Remarks
1550	[Ohm]	1	[V]	-
1000	[Ohm]	2	[V]	-
560	[Ohm]	3	[V]	-
47	[Ohm]	4	[V]	Default setting PT62SCMD12

© 2014 Prodrive Technologies B.V.



Figure 4-3, Location R_{OCP} and R_{BLANK}

IMPORTANT INFORMATION AND DISCLAIMER

This datasheet is made available for your convenience only and may be updated without notice. Prodrive Technologies makes no representation or warranty as to the accuracy of the data provided. Products are only sold subject to Prodrive Technologies terms and conditions of sale. Products are not intended for military, space, aircraft or life support applications unless explicitly agreed in writing otherwise. Your use of these data remains solely your responsibility. In no event shall Prodrive Technologies liability arising out of this datasheet exceed the purchase price paid for the products concerned.

For more technical or commercial information visit: http://www.prodrive-technologies.com or send an email to power@prodrive-technologies.com

© 2014 Prodrive Technologies B.V. All rights reserved. Reproduction is prohibited without prior written consent.